

19 / 05 / 2010

SDEV-FICA 51 R1

DESIGNATION	Telis 1 Mod/Var RTS Pure
REFERENCE	1810974
RANGE	RTS New Collection

FUNCTIONS

One channel hand held transmitter dedicated to the Mod/Var Receivers.



Also compatible with all RTS receivers, in that case the tilting is made with the up or down keys (wheel not fonctionnal).

TECHNICAL SPECIFICATIONS

Box	Material Color Size Protection factor against solid & splashproof	ABS and SEBS White / Grey 144.7 x 48.5 x 25.5 mm I.P. 30
Battery	Voltage Type	3 V 2430 Lithium
Battery life time (at ambient temperature)		2 years (20 actions of 0,5" per day)
Frequency Radiated power Modulation type		433.42 Mhz +/- 100 kHz 0 dBm or 1 mW 100% modulation On Off Keying
Protocole		RTS
Standard		EN 60730 - 2 - 1 EN 300220 - 3 EN 301489 - 3
Temperature range	Storage Working	-20 °C / +70 °C 0 °C / +45 °C
Antenna		Integrated
Drop resistance		1.5 m
Wear resistance		250 cycles of abrasion with a jean
Cleaning products resistivity		product for glass (with alcohol)
Weight		approx. 70g